



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE5511 thru NTE5513 Silicon Controlled Rectifier (SCR) 5 Amp, TO66

Description:

The NTE5511 thru NTE5513 all-diffused, three junction, silicon controlled rectifiers (SCR's) are intended for use in power-control and power-switching applications. These devices are available in a TO66 type package and have a blocking voltage capability of up to 600V and a forward current rating of 5A (rms value) at a case temperature of +75°C.

Features:

- Designed Especially for High-Volume Systems
- Readily Adaptable for PC Boards and Metal Heat Sinks
- Low Switching Losses
- High di/dt and dv/dt Capabilities
- Shorted Emitter Gate-Cathode Construction
- Forward and Reverse Gate Dissipation Ratings
- All-Diffused Construction Assures Exceptional Uniformity and Stability of Characteristics
- Direct-Soldered Internal Construction Assures Exceptional Resistance to Fatigue
- Symmetrical Gate-Cathode Construction Provides Uniform Current Density, Rapid Electrical Conduction, and Efficient Heat Dissipation
- All-Welded Construction and Hermetic Sealing
- Low Leakage Currents, Forward and Reverse
- Low Forward Voltage Drop at High Current Levels
- Low Thermal Resistance

Absolute Maximum Ratings: (For Operation with Sinusoidal AC Supply Voltage at a Frequency between 50Hz and 400Hz, and with Resistive or Inductive Load)

Transient Peak Reverse Voltage (Non-Repetitive), V_{RM} (non-rep)	
NTE5511	330V
NTE5512	660V
NTE5513	700V
Peak Reverse Voltage (Repetitive), V_{RM} (rep)	
NTE5511	200V
NTE5512	400V
NTE5513	600V
Peak Forward Blocking Voltage (Repetitive), V_{FBOM} (rep)	
NTE5511	600V
NTE5512	600V
NTE5513	700V
Average DC Forward Current, $I_{F(av)}$ ($T_C = +75^\circ C$ mounted on heat sink, conduction angle or 180°)	
	3.2A
RMS Forward Current ($T_C = +75^\circ C$ mounted on heat sink), I_{FRMS}	
	5A
Peak Surge Current (For one cycle of applied voltage), $i_{FM(surge)}$	
	60A
Sub-Cycle Surge (Non-Repetitive, for a period of 1ms to 8.3ms), I^2t	
	15A ² sec
Rate of Change of Forward Current (Note 1), di/dt	
	200A/ μ s
Gate Power (Peak, Forward, or Reverse, for 10 μ s duration, Note 2), P_{GM}	
	13W
Average Gate Power (Note 2), P_{GAV}	
	500mW
Operating Case Temperature Range, T_C	
	-40° to +100°C
Storage Temperature Range, T_{stg}	
	-40° to +125°C

Note 1. $V_{FB} = V_{BOO}$ (min value), $I_{GT} = 200mA$, 0.5 μ s rise time
 Note 2. Any values of peak gate current or peak gate voltage to give the maximum gate power is permissible.

Electrical Characteristics: (At Maximum Ratings, $T_C = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Forward Breakover Voltage NTE5511	V_{BOO}	$T_C = +100^\circ\text{C}$	200	-	-	V	
NTE5512			400	-	-	V	
NTE5513			600	-	-	V	
Peak Blocking Forward Current NTE5511	I_{FBOM}	$V_{FBO} = 200\text{V}$	$T_C = +100^\circ\text{C}$	-	0.10	1.5	mA
NTE5512		$V_{FBO} = 400\text{V}$		-	0.20	3.0	mA
NTE5513		$V_{FBO} = 600\text{V}$		-	0.40	4.0	mA
Peak Blocking Reverse Current NTE5511	I_{RBOM}	$V_{RBO} = 200\text{V}$	$T_C = +100^\circ\text{C}$	-	0.05	0.75	mA
NTE5512		$V_{RBO} = 400\text{V}$		-	0.10	1.5	mA
NTE5513		$V_{RBO} = 600\text{V}$		-	0.20	2.0	mA
Forward Voltage Drop	V_F	$I_F = 30\text{A}$	-	2.15	2.80	V	
DC Gate-Trigger Current	I_{GT}		-	8	15	mA	
DC Gate-Trigger Voltage	V_{GT}		-	1.2	2.0	V	
Holding Current	I_{Hold}		-	10	20	mA	
Critical Rate of Applied Forward Voltage	dv/dt	$V_{FB} = v_{BOO}$ (min), exponential rise, $T_C = +100^\circ\text{C}$	10	200	-	V/ μs	
Turn-On Time (Delay Time + Rise Time)	t_{on}	$V_{FB} = v_{BOO}$ (min), $i_F = 4.5\text{A}$, $I_{GT} = 200\text{mA}$, $0.1\mu\text{s}$ rise time	0.75	1.5	-	μs	
Turn-Off Time (Reverse Recovery Time + Gate Recovery Time)	t_{off}	$i_F = 2\text{A}$, $50\mu\text{s}$ pulse width, $dv_{FB}/dt = 20\text{V}/\mu\text{s}$, $di_r/dt = 30\text{A}/\mu\text{s}$, $I_{GT} = 200\text{mA}$, $T_C = +75^\circ\text{C}$	-	15	50	μs	
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$		-	-	4	$^\circ\text{C}/\text{W}$	

