



Features:

- **Now includes 8mm and 10mm sizes in addition to 1.8mm, 3mm, and 5mm!**
- **Surface Mount now includes Super Bright White!**
- **Complete color selection including pink and purple!**

NTE Type Number	Individual Package Size	Typical Viewing Angle (°)	Viewed Color	Lens Type	Typical Luminous Intensity (mcd) I_V	Typical Forward Voltage-Drop (Volts) V_F	Maximum Reverse Breakdown Voltage (Volts) V_R	Maximum DC Forward Current (mA) I_F	Maximum Power Dissipation (mW) P_D
30005	0603 (SMT)	120	Super Red	Water Clear	100	1.85	5	30	100
30006	0603 (SMT)	120	Super Green	Water Clear	15	2.2	5	25	105
30018	0603 (SMT)	140	Super Orange	Water Clear	75	2.0	5	25	100
30019	0603 (SMT)	140	Super Blue	Water Clear	52	3.5	4	20	120
30020	0603 (SMT)	140	Super White	Yellow Diffused	370	3.5	4	20	120
30003	0805 (SMT)	120	Super Green	Water Clear	15	2.2	5	25	105
30022	0805 (SMT)	140	Super Orange	Water Clear	70	2.0	5	25	100
30023	0805 (SMT)	140	Super Blue	Water Clear	52	3.5	4	20	120
30024	0805 (SMT)	140	Super White	Yellow Diffused	600	3.5	4	20	120
30074	1206 (SMT)	140	Super Red	Water Clear	100	2.0	5	25	100
30075	1206 (SMT)	140	Super Green	Water Clear	220	3.5	5	20	120
30076	1206 (SMT)	140	Super Yellow	Water Clear	100	2.0	5	25	100
30077	1206 (SMT)	140	Super Orange	Water Clear	100	2.0	5	25	100
30078	1206 (SMT)	140	Super Blue	Water Clear	48	3.5	4	20	120
30079	1206 (SMT)	140	Super White	Yellow Diffused	350	3.5	4	20	120
30081	Right Angle (SMT)	120	Super Red	Water Clear	37.5	1.8	5	30	110
30082	Right Angle (SMT)	120	Super Green	Water Clear	13.5	2.15	5	25	84
30083	Right Angle (SMT)	140	Super Yellow	Water Clear	60	2.0	5	25	100
30084	Right Angle (SMT)	120	Super Orange	Water Clear	60	2.0	5	25	100
30085	Right Angle (SMT)	120	Super Blue	Water Clear	60	3.5	4	20	120
30011	PLCC (SMT)	120	Super Red	Water Clear	150	1.85	5	30	105
30012	PLCC (SMT)	120	Super Green	Water Clear	25	2.2	5	25	105
30026	PLCC (SMT)	120	Super Orange	Water Clear	60	2.0	5	25	100
30027	PLCC (SMT)	120	Super Blue	Water Clear	48	3.5	4	20	120
30028	PLCC (SMT)	120	Super White	Yellow Transparent	900	3.5	4	30	120
30088	SOT-23 (SMT)	140	Super Red	Water Clear	12	1.8	5	30	110
3004	T-3/4 (1.8mm)	60	Super Red	Red Diffused	45	1.9	5	25	105
3137	T-3/4 (1.8mm)	24	Super Red	Water Clear	1500	2.0	5	25	100
3138	T-3/4 (1.8mm)	24	Super Red	Water Clear	1200	1.66	5	25	110
3136	T-3/4 (1.8mm)	24	Super Orange	Water Clear	1300	2.0	5	25	100

NTE Type Number	Individual Package Size	Typical Viewing Angle (°)	Viewed Color	Lens Type	Typical Luminous Intensity (mcd) I _V	Typical Forward Voltage-Drop (Volts) V _F	Maximum Reverse Breakdown Voltage (Volts) V _R	Maximum DC Forward Current (mA) I _F	Maximum Power Dissipation (mW) P _D
3134	T-3/4 (1.8mm)	24	Super Yellow	Water Clear	1300	2.0	5	25	100
30009	T-3/4 (1.8mm)	20	Super Green	Water Clear	100	2.2	5	25	105
3133	T-3/4 (1.8mm)	24	Super Yellow/Green	Water Clear	900	2.2	5	25	100
3132	T-3/4 (1.8mm)	24	Super High-Eff Yellow/Green	Water Clear	500	2.15	5	25	84
3139	T-3/4 (1.8mm)	24	Super Blue	Water Clear	1500	3.5	4	25	120
30034	T-1 (3mm)	19	Super Deep Red	Water Clear	2000	1.86	5	25	110
30035	T-1 (3mm)	10	Super Amber	Water Clear	2500	2.0	5	25	100
30033	T-1 (3mm)	10	Super Orange	Water Clear	2500	2.0	5	25	100
30032	T-1 (3mm)	10	Super Yellow	Water Clear	250	2.0	5	25	100
30031	T-1 (3mm)	14	Super Pure Green	Water Clear	5000	3.5	5	30	120
30030	T-1 (3mm)	14	Super Yellow/Green	Water Clear	1600	2.2	5	25	100
30036	T-1 (3mm)	15	Super Blue	Water Clear	3000	3.5	5	30	120
30120	T-1 (3mm)	25	Super Purple	Water Clear	75	3.3	5	20	120
30125	T-1 (3mm)	30	Super Pink	Water Clear	1000 Max	3.3	5	30	120
30044	T-1 (3mm)	30	Super White	Water Clear	7000	3.6	5	30	120
30041	T-1 3/4 (5mm)	12	Super Deep Red	Water Clear	3500	1.86	5	25	110
30040	T-1 3/4 (5mm)	40	Super Orange	Water Clear	5500	2.0	5	25	100
30042	T-1 3/4 (5mm)	12	Super Amber	Water Clear	5500	2.0	5	25	100
30039	T-1 3/4 (5mm)	12	Super Yellow	Water Clear	7000	2.25	5	30	100
30038	T-1 3/4 (5mm)	15	Super Pure Green	Water Clear	10500	3.5	5	30	120
30037	T-1 3/4 (5mm)	12	Super Yellow/Green	Water Clear	2500	2.2	5	25	100
30043	T-1 3/4 (5mm)	12	Super Blue	Water Clear	3500	3.5	5	30	120
30121	T-1 3/4 (5mm)	20	Super Purple	Water Clear	300	3.3	5	30	80
30126	T-1 3/4 (5mm)	35	Ultra Bright Pink	Water Clear	4000	3.45	5	30	120
30127	T-1 3/4 (5mm)	15	Super Turquoise	Water Clear	10000	3.2	5	20	70
30045	T-1 3/4 (5mm)	22	Super White	Water Clear	16000	3.6	5	30	120
30056	8mm	25	Super Light Red	Water Clear	3600	2.0	5	25	100
30057	8mm	30	Super Deep Red	Water Clear	2200	1.86	5	25	110
30055	8mm	25	Super Orange	Water Clear	3600	2.0	5	25	100
30054	8mm	30	Super Light Green	Water Clear	4500	3.5	4	25	120
30053	8mm	25	Super Yellow/Green	Water Clear	1600	2.2	5	25	100
30058	8mm	35	Super Blue	Water Clear	1500	3.5	4	25	120
30123	8mm	25	Super Purple	Water Clear	190	3.3	5	20	120
30059	8mm	30	Super White	Water Clear	4000	3.5	4	25	120
30068	T-3 1/4 (10mm)	40	Super Light Red	Water Clear	2000	2.0	5	25	100
30069	T-3 1/4 (10mm)	40	Super Deep Red	Water Clear	3000	1.86	5	25	110
30067	T-3 1/4 (10mm)	40	Super Orange	Water Clear	2000	2.0	5	25	100
30066	T-3 1/4 (10mm)	40	Super Light Green	Water Clear	3500	3.5	4	30	120
30065	T-3 1/4 (10mm)	40	Super Yellow Green	Water Clear	1300	2.2	5	25	100
30070	T-3 1/4 (10mm)	40	Super Blue	Water Clear	1200	3.5	5	25	120
30124	T-3 1/4 (10mm)	20	Super Purple	Water Clear	180	3.3	5	30	80
30071	T-3 1/4 (10mm)	40	Super White	Water Clear	4000	3.5	4	25	120

Distributed By:

NTE Electronics, Inc.
44 Farrand Street
Bloomfield, NJ 07003

Phone: 973-748-5089
Fax: 973-748-6224
www.nteinc.com

