

NTE1906 Integrated Circuit Positive 3 Terminal Voltage Regulator, 18V, 100mA

Description:

The NTE1906 is a positive 3-terminal voltage regulator in a TO92 type package suitable for numerous applications requiring up to 100mA. This device features thermal shutdown and current limiting making the NTE1906 remarkably rugged. In most applications, no external components are required.

The NTE1906 is useful for on-card regulation or any other application where a regulated positive voltage at a modest current level is needed. This device offers a substantial advantage over the common resistor/zenor diode approach.

Features:

- Internal Short-Circuit Current Limiting
- Internal Thermal Overload Protection
- No External Components Required

Absolute Maximum Ratings:

Input Voltage, V_I 35V
 Internal Power Dissipation (Note 1), P_D Internally Limited
 Operating Junction Temperature Range, T_{opr} 0° to +70°C
 Maximum Junction Temperature, T_J +125°C
 Storage Junction Temperature Range, T_{stg} -55° to +150°C
 Lead Temperature (During Soldering, 10sec), T_L +300°C

Note 1. Thermal resistance, junction-to-ambient is 180°C/W when mounted with 0.4" leads on a PC board and 160°C/W when mounted with .250" leads on a PC board.

Electrical Characteristics: ($V_I = 27V$, $I_O = 40mA$, $C_I = 0.33\mu F$, $C_O = 0.1\mu F$, $0^\circ < T_J < +125^\circ C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V_O	$T_J = +25^\circ C$	17.3	18.0	18.7	V
		$20.7V \leq V_I \leq 33V$, $1mA \leq I_O \leq 100mA$	17.1	18.0	18.9	V
Line Regulation	Reg_{line}	$T_J = +25^\circ C$, $20.7V \leq V_I \leq 33V$	-	-	325	mV

Electrical Characteristics (Cont'd): ($V_I = 27V$, $I_O = 40mA$, $C_I = 0.33\mu F$, $C_O = 0.1\mu F$, $0^\circ < T_J < +125^\circ C$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Load Regulation	Reg_{load}	$T_J = +25^\circ C$, $1mA \leq I_O \leq 100mA$	-	-	170	mV
Quiescent Current	I_B	$T_J = +125^\circ C$	-	2	6	mA
Quiescent Current Change	ΔI_B	With line, $21V \leq V_I \leq 33V$	-	-	1.5	mA
		With load, $1mA \leq I_O \leq 40mA$	-	-	0.1	mA
Output Noise Voltage	V_n	$T_J = +25^\circ C$, $f = 10Hz$ to $10kHz$	-	150	-	μV
Long-Term Stability	$\Delta V_O/\Delta t$		-	56	-	mV/1kHrs
Ripple Rejection	RR	$f = 120Hz$, $23V \leq V_I \leq 33V$	33	48	-	dB
Dropout Voltage	V_{DO}	$T_J = +25^\circ C$, $I_O = 40mA$	-	1.7	-	V

